

mobiBLUE-450 I-ZVMU

12 V-30 l/min



Item number: 26 901
EAN: 4250979602132
Discount group: D

Technical data

Tank volume (l): 450
 Material tank: LLDPE (linear low density polyethylene)
 Color tank: white
 Colour of cover: blue, RAL 5015

Pump

Connecting cable, length (m): 3
 Hydraulic data
 Pump design: diaphragm pump, selfpriming

Delivery rate under free discharge (l/min): 30
 Discharge pressure up to (bar): 1,7
 Pumping media: AdBlue®, water

Motor data

Voltage (V): 12 V DC
 Power consumption (A): 18
 Duty cycle (min) under free discharge max.: 180
 Safety class: IP66



Dimensions LxWxH (mm): 1200 x 800 x 912
 Weight (kg): 56

Specification

- Single-walled tank (45 319)
- Universal fixation loops for integral shackles (89 823)
- Lockable protection cap (81 579)
- Ventilation valve (45 150)
- Tank cap with seal (45 152)
- Diaphragm pump, selfpriming (25 281)
- On/Off switch
- Connecting cable with battery terminal clips and fuse holder (80 725)
- Mechanical control nozzle for AdBlue® (ZVMU) (23 163 878)
- AdBlue® discharge hose, DN 19, 4 m / 13.1 ft, with hose fitting G 1" female and swivel joint for ZVMU (25 674)
- AdBlue® suction hose with siphon protection (25 661)

Special notes

- Movable under load
- Diffusion resistant
- UV-resistant
- Transparent tank (fill level is recognizable)
- Can be moved while filled with a forklift or crane
- Compact construction (fits on a Euro pallet)
- Pump area closed with a cover to protect against weather conditions



- High quality equipment
- Manufacturer's warranty on the tank, valid for 5 years from the date of delivery, and 2 years warranty on built-in and attachment parts

Packaging

Dimensions LxWxH (mm):	1200 x 800 x 912
Weight including package (kg):	56
Packing unit:	1,0